



EKSELANS BY ITS

CABLE COAXIAL CC 596 / CC112 / CC11

Factor de apantallamiento clase A

REFERENCIA		CC 596	CC 112	CC 11
Código		151005	151006	151007
Conductor interno	mm	0,8 CCS	1.0 CCS	1,63 CCS
Dieléctrico	mm	3,2	4,60	7,24
Lámina		AL/PET/AL	AL/PET/AL	AL/PET/AL
Malla	Wires	96/AL	112/AL	128/AL
Cubierta exterior diámetro	mm	5.0/PVC	6,6-6,7 / PVC	10.3/PVC
Color		BL	BL	N
Atenuación	dB/50MHz	6,3	4,7	2,8
	dB/100MHz	8,4	6,4	4,9
	dB/230MHz	11,4	9,1	5,9
	dB/470MHz	18,4	13,2	8,8
	dB/860MHz	25,2	17,9	11,9
	dB/950MHz	26,6	19,1	12,6
	dB/1350MHz	32,1	23,4	15,6
	dB/1750MHz	36,6	26,7	17,9
	dB/2150MHz	39,9	29,6	19,8
Apantallamiento	dB/5-1000MHz	90	90	90
	dB/1000-2400MHz	85	85	85
	dB/3000MHz	75	75	75
Bobina	m	100	100	300

