

Product Detail Page



PA-702

Order-No.: 17.1330

Mono PA mixing amplifier

- 1 x 35 W
- Silent operation due to fanless cooling concept
- 2 low-impedance microphone inputs
- 1 aux input, 1 phono input, switchable
- Speaker outputs via spring-loaded terminals
- Input and output level controls
- 3-way equalizer for the output
- Connection for a microphone talk button to switch off the other sources during announcements
- Mains operation

Specifications

Channels	3
Zones	-
Power rating	35 W
Power rating at 2 Ω	-
Power rating at 4 Ω	-
Power rating at 8 Ω	-
Power rating at 100 V	-
Power rating with 4 Ω bridged operation	-
Power rating with 8 Ω bridged operation	-
Peak music power output (PMAX)	70 W
Inputs	2 mV (mic), 150 mV (aux), 3 mV (phono)
Frequency range	65-16,000 Hz, ±3 dB
Crossover network	-
Crossover frequency	-
Integrated limiter	-
Equalizer bass	±10 dB/150 Hz
Equalizer midrange	±10 dB/1 kHz



Equalizer treble	±10 dB/6 kHz
S/N ratio	> 55 dB
Crosstalk attenuation	-
THD	< 2 %
Power supply	~ 230 V/50 Hz/92 VA
Mains voltage	~ 230 V
	50 Hz
	92 VA
	-
Standby current	-
Alternative operating voltage	-
Alternative power supply	-
Admiss. ambient temp.	0-40 °C
Dimensions	320x85x230 mm
Width	320 mm
Height	85 mm
Depth	230 mm
Rack spaces, RS	-
Weight	4.5 kg
Connections	2 x 6.3 mm jack (mic), 1 x RCA L/R (aux), 1 x RCA L/R (phono), connecting terminals (speakers)

