Product Detail Page







VMX-440/SW

Order-No : 20.2530

4-channel microphone line mixer

Mixing made easy! An easy-to-use operating concept and clearly arranged features. Two stereo line sources and two mono microphone sources can be mixed together without any problems. Each input channel features a tone control. The master output levels can be preadjusted via recessed trimming potentiometers in order to protect them against overload. An optional remote switch can mute the stereo master outputs.

- 2 stereo line inputs
- 2 balanced microphone inputs
- · Parallel stereo line input on the front panel
- 3-way equalizer for each microphone input
- Common 2-way tone control for the two line inputs
 Muting via optional momentary push-button/switch
- 2 adjustable stereo master outputs
- Master output level can be preadjusted via trimming potentiometers
- Adjustable headphone output
- Stereo record output
- 482 mm (19") rack installation, 1 RS, with supplied mounting brackets

Specifications

No. of channels	
No. of inputs	
Mic input	1 mV/600 Ω, 2 x 6.3 mm jack, bal.
Line input	100 mV/10 kΩ, 3 x RCA L/R
CD input	<u>-</u>
Phono input	-
Tape (play)	-
Aux input	-
Insert input	-
effect return	-
Master output	1-3 V/100 Ω, 2 x RCA L/R
Record output	1 V/100 Ω, 1 x RCA L/R
Monitor output	-
Booth output	-
Aux output	-









Insert output	-			
effect send	-			
Control room	-			
Tape (rec)	-			
Headphones	\geq 32 Ω , 2 x 15 mW, 1 x 6.3 mm jack			
Gooseneck lamp	-			
USB	-			
Frequency range	20-20,000 Hz			
THD	0.05 %			
S/N ratio	> 60 dB			
Crosstalk	-			
Equalizer bass	±12 dB/30 Hz			
Equalizer midrange	±12 dB/1 kHz (voice only)			
Equalizer treble	±12 dB/12 kHz			
equalizer	-			
Talkover	-			
Phantom power	-			
Crossfader	-			
Media player	-			
Amplifier	-			
Power supply	230 V~/50 Hz/10 VA			
Mains voltage	~ 230 V			
	50 Hz			
	10 VA			
Alternative operating voltage	-			









Alternative power supply	-	
Width	482 mm	
Height	45 mm	
Depth	180 mm	
Rack spaces, RS	1	
Weight	2.9 kg	







