



CODIGO		9060031	9060032	9060043	9060044
MODELO		FP-211	FP-217	FP-223	FP-226
Conexión		F hembra			
Salidas		2			
Rango de frecuencias	MHz	5 - 2400			
Atenuación de derivación ①	dB ±2,0	5-862 MHz 11,0 930-2150 MHz 11,0 2150-2400 MHz 12,0	17,0 17,0 18,5	23,0 23,0 24,0	26,0 26,0 26,0
Atenuación de paso ②	dB ±0,5	5-862 MHz 2,5 930-2150 MHz 2,5-4,0 2150-2400 MHz 4,0-4,5	1,8 1,8-3,0 3,0-3,5	1,6 1,6-2,6 2,6-3,3	
Directividad ④	dB	5-862 MHz >15,0 930-2150 MHz >5,0 2150-2400 MHz >5,0	>17,0 >5,0 >5,0	>18,0 >5,0 >5,0	
Desacoplo ⑤	dB	5-862 MHz >30,0 930-2150 MHz >22,0 2150-2400 MHz >20,0	>30,0 >25,0 >25,0	>40,0 >35,0 >35,0	>50,0 >40,0 >40,0
Pérdidas de retorno	dB	5-862 MHz >12,0 930-2150 MHz >12,0 2150-2400 MHz >15,0	>15,0 >15,0 >15,0	>17,0 >15,0 >15,0	
Unidades por embalaje		6			
Peso embalaje	Kg	0,45			
Dimensiones embalaje	mm	155 x 95 x 40			