



CODIGO		9060053		9060033		9060034		9060035	
MODELO			FD-210	FD-213		FD-219		FD-225	
Conexión			F hembra						
Salidas			2						
Rango de frecuencias	MHz		5 - 2400						
Atenuación de derivación									
①	dB ±1,0	5-47 MHz 47-230 MHz 470-862 MHz 950-2150 MHz 2150-2400 MHz	26,0-24,5 24,5-21,5 17,0-13,0 12,5-8,5 8,5-8,0	28,0 28,0-25,0 21,5-17,5 17,0-12,0 12,0-11,5		32,0 32,0-30,5 27,5-24,0 23,0-17,5 17,5-17,0		36,0 36,0-34,5 33,0-30,0 30,0-26,0 26,0-25,5	
Planitud en banda	dB		±1,0						
Atenuación de paso									
②	dB ±0,5	5-47 MHz 47-230 MHz 470-862 MHz 950-2150 MHz 2150-2400 MHz	0,8 0,8-1,0 1,2-1,7 1,8-3,0 3,0-3,5	0,6 0,6-0,7 0,9-1,2 1,2-2,0 2,0-2,3		0,5 0,5 0,5-0,8 0,8-1,4 1,4-1,6		0,5 0,5 0,5-0,6 0,6-1,0 1,2	
Directividad									
④	dB	5-47 MHz 47-862 MHz 950-2150 MHz 2150-2400 MHz	>0 >0-6 >7 >8	>0 >0-5 >5-8 >8		>0 >0-5 >5-7 >7		>0 >0-4 >4-7 >8	
Desacoplo									
⑤	dB	5-47 MHz 47-862 MHz 950-2150 MHz 2150-2400 MHz	>45 >32 >28 >26	>50 >40 >30 >28		>60 >55 >45 >38		>60 >60 >45 >40	
Pérdidas de retorno									
	dB	5-47 MHz 47-862 MHz 950-2150 MHz 2150-2400 MHz	>18 >18 >13 >13	>17 >15 >15 >13		>18 >18 >15 >13			
Unidades por embalaje			6						
Peso embalaje	Kg		0,45						
Dimensiones embalaje	mm		155 x 95 x 40						