



CODIGO		9060053		9060033		9060034		9060035					
MODELO		FD-210		FD-213		FD-219		FD-225					
Conexión				F hembra									
Salidas				2									
Rango de frecuencias		MHz		5 - 2400									
Atenuación de derivación													
①		dB ±1,0		5-47 MHz 47-230 MHz 470-862 MHz 950-2150 MHz 21 50-2400 MHz		26,0-24,5 24,5-21,5 17,0-13,0 12,5-8,5 8,5-8,0		28,0 28,0-25,0 21,5-17,5 17,0-12,0 12,0-11,5		32,0 32,0-30,5 27,5-24,0 23,0-17,5 17,5-17,0		36,0 36,0-34,5 33,0-30,0 30,0-26,0 26,0-25,5	
Planitud en banda		dB		±1,0									
Atenuación de paso													
②		dB ±0,5		5-47 MHz 47-230 MHz 470-862 MHz 950-2150 MHz 21 50-2400 MHz		0,8 0,8-1,0 1,2-1,7 1,8-3,0 3,0-3,5		0,6 0,6-0,7 0,9-1,2 1,2-2,0 2,0-2,3		0,5 0,5 0,5-0,8 0,8-1,4 1,4-1,6		0,5 0,5 0,5-0,6 0,6-1,0 1,2	
Directividad													
④		dB		5-47 MHz 47-862 MHz 950-2150 MHz 21 50-2400 MHz		>0 >0-6 >7 >8		>0 >0-5 >5-8 >8		>0 >0-5 >5-7 >7		>0 >0-4 >4-7 >8	
Desacoplo													
⑤		dB		5-47 MHz 47-862 MHz 950-2150 MHz 21 50-2400 MHz		>45 >32 >28 >26		>50 >40 >30 >28		>60 >55 >45 >38		>60 >60 >45 >40	
Pérdidas de retorno													
		dB		5-47 MHz 47-862 MHz 950-2150 MHz 21 50-2400 MHz		>18 >18 >13 >13		>17 >15 >15 >13		>18 >18 >15 >13			
Unidades por embalaje				6									
Peso embalaje		Kg		0,45									
Dimensiones embalaje		mm		155 x 95 x 40									