



CODIGO			9060036	9060037	9060041	9060042
MODELO			FI-243	FI-473	FI-253	FI-483
Conexión			F hembra			
Salidas			2	4	2	4
Rango de frecuencias	MHz		5 - 2400			
Atenuación de distribución						
①	dB ±1,0	5-13 MHz	5,0-5,0	10,0-10,0	5,0-5,0	14,0-9,5
		13-47 MHz	5,0-4,0	10,0-9,0	5,0-4,5	9,5-9,5
		47-862 MHz	4,0-4,0	9,0-9,0	4,5-4,0	9,5-8,0
		950-2150 MHz	4,0-5,5	9,0-10,5	4,0-4,0	8,0-10,5
		2510-2400 MHz	5,5-6,0	10,5-12,0	4,0-4,5	10,5-12,5
Planitud en banda	dB		±0,3			±0,5
Desacoplo						
②	dB	5-13 MHz	>20	>26	>9	>14
		13-47 MHz	>20	>26	>13	>14
		47-862 MHz	>19	>16	>13	>12
		950-2150 MHz	>19	>16	>15	>8
		2510-2400 MHz	>20	>14	>16	>6
Pérdidas de retorno						
	dB	5-13 MHz	>14	>18	>13	-
		13-47 MHz	>14	>18	>14	>11
		47-862 MHz	>16	>12	>15	>11
		950-2150 MHz	>13	>17	>13	>11
		2510-2400 MHz	>19	>14	>16	>9
Unidades por embalaje			6			
Peso embalaje	Kg		0,45			
Dimensiones embalaje	mm		155 x 95 x 40			