



CODIGO		9060054	9060038	9060039	9060040
MODELO		FD-410	FD-413	FD-419	FD-425
Conexión		F hembra			
Salidas		4			
Rango de frecuencias	MHz	5 - 2400			
Atenuación de derivación ①	dB ±1,0	5-47 MHz 47-230 MHz 470-862 MHz 950-2150 MHz 2150-2400 MHz 27,0-25,5 25,5-22,5 18,8-15,0 14,5-10,2 10,2-9,7	28,0 28,0-26,0 22,5-18,5 18,0-13,5 13,5	33,0 33,0-31,0 28,0-24,0 23,5-18,5 18,5-17,5	36,0 36,0-34,5 32,5-30,0 30,0-25,5 25,5-25,0
Planitud en banda	dB	±1,0			
Atenuación de paso ②	dB ±0,5	5-47 MHz 47-230 MHz 470-862 MHz 950-2150 MHz 2150-2400 MHz 1,5-1,7 1,7-1,8 2,1-2,7 2,9-4,7 4,7-5,0	1,0 1,0-1,3 1,5-2,0 2,0-3,0 3,0-3,5	0,5 0,5-0,8 0,9-1,0 1,2-1,8 1,8-2,0	0,5 0,5-0,6 0,7-0,9 0,9-1,3 1,3-1,5
Directividad ④	dB	5-47 MHz 47-862 MHz 950-2150 MHz 2150-2400 MHz >0 >0-6 >6 >7	>0 >0-6 >6 >6		>0 >0-5 >5-7 >7
Desacoplo ⑤	dB	5-47 MHz 47-862 MHz 950-2150 MHz 2150-2400 MHz >45 >35 >30 >30	>50 >40 >32 >32	>60 >55 >45 >40	>60 >60 >45 >40
Pérdidas de retorno	dB	5-47 MHz 47-862 MHz 950-2150 MHz 2150-2400 MHz >15 >15 >13 >13	>15 >16 >16 >16	>17 >18 >17 >15	>18 >18 >17 >16
Unidades por embalaje		6			
Peso embalaje	Kg	0,45			
Dimensiones embalaje	mm	155 x 95 x 40			