



DISPONIBLE
AVAILABLE

VODA



SIMPLE>>

<<DOBLE

	Mod.	IP				
1X9	SIMPLE 60 CM	65		650X72X86mm	EC-3640	15ud.
1X18	SIMPLE 120 CM	65		1265X72X86mm	EC-3641	12ud.
1X24	SIMPLE 150 CM	65		1565X72X86mm	EC-3642	12ud.
2X9	DOBLE 60 CM	65		650X115X86mm	EC-3643	20ud.
2X18	DOBLE 120 CM	65		1265X115X86mm	EC-3644	8ud.
2X24	DOBLE 150CM	65		1565X115X86mm	EC-3645	8ud.

VODA SIMPLE




VODA DOBLE



SIMPLE 60CM



SIMPLE 120CM



SIMPLE 150CM



DOBLE 60CM



DOBLE 120CM



DOBLE 150CM



DISPONIBLE
AVAILABLE

AQUA

IK10



"Extruded Fire Retardant Polycarbonate.
Molding in one."

	⚡	CCT	💡	IP	📐	🌒	🕒	📊	📦
20W	220-277V	3.000K	1.500 lm	65	120°	—	●	EC-2731	2ud.
20W	220-277V	4.200K	1.580 lm	65	120°	—	●	EC-2721	2ud.
20W	220-277V	5.500K	1.650 lm	65	120°	—	●	EC-2722	2ud.
40W	220-277V	3.000K	3.050 lm	65	120°	—	●	EC-2724	2ud.
40W	220-277V	4.200K	3.100 lm	65	120°	—	●	EC-2725	2ud.
40W	220-277V	5.500K	3.200 lm	65	120°	—	●	EC-2726	2ud.
50W	220-277V	3.000K	3.850 lm	65	120°	—	●	EC-2728	2ud.
50W	220-277V	4.200K	3.900 lm	65	120°	—	●	EC-2729	2ud.
50W	220-277V	5.500K	4.000 lm	65	120°	—	●	EC-2730	2ud.

20W




40W




50W







AQUA 20W



AQUA 40W



AQUA 50W



CHIP: EPSTAR

CRI>80

PF≥0,9

-20°C
+50°C

ecotic

40.000h

100K ON/OFF LED