



CODIGO			9060031		9060032		9060043		9060044	
MODELO			FP-211		FP-217		FP-223		FP-226	
Conexión			F hembra							
Salidas			2							
Rango de frecuencias		MHz	5 - 2400							
Atenuación de derivación			11,0		17,0		23,0		26,0	
①	dB ±2,0	5-862 MHz	11,0		17,0		23,0		26,0	
		930-2150 MHz	11,0		17,0		23,0		26,0	
		2150-2400 MHz	12,0		18,5		24,0		26,0	
Atenuación de paso			2,5		1,8		1,6			
②	dB ±0,5	5-862 MHz	2,5		1,8		1,6			
		930-2150 MHz	2,5-4,0		1,8-3,0		1,6-2,6			
		2150-2400 MHz	4,0-4,5		3,0-3,5		2,6-3,3			
Directividad			>15,0		>17,0		>18,0			
④	dB	5-862 MHz	>15,0		>17,0		>18,0			
		930-2150 MHz	>5,0		>5,0		>5,0			
		2150-2400 MHz	>5,0		>5,0		>5,0			
Desacoplo			>30,0		>30,0		>40,0		>50,0	
⑤	dB	5-862 MHz	>30,0		>30,0		>40,0		>50,0	
		930-2150 MHz	>22,0		>25,0		>35,0		>40,0	
		2150-2400 MHz	>20,0		>25,0		>35,0		>40,0	
Pérdidas de retorno			>12,0		>15,0		>17,0			
	dB	5-862 MHz	>12,0		>15,0		>17,0			
		930-2150 MHz	>12,0		>15,0		>15,0			
		2150-2400 MHz	>15,0		>15,0		>15,0			
Unidades por embalaje			6							
Peso embalaje		Kg	0,45							
Dimensiones embalaje		mm	155 x 95 x 40							