



CODIGO			9060046		9060047		9060048	
MODELO			FP-414		FP-420		FP-426	
Conexión			F hembra					
Salidas			4					
Rango de frecuencias	MHz		5 - 2400					
Atenuación de derivación ①	dB ±2,0	5-862 MHz 930-2150 MHz 2150-2400 MHz	14,0 14,0 15,0		20,0 20,0 20,5		26,0 26,0 25,0	
Atenuación de paso ②	dB ±0,5	5-862 MHz 930-2150 MHz 2150-2400 MHz	4,5 4,5-5,7 5,7-6,5		1,2 1,2-2,6 2,6-3,0		0,8 0,8-1,8 1,8-2,3	
Directividad ④	dB	5-862 MHz 930-2150 MHz 2150-2400 MHz	>13,0 >10,0 >10,0			>18,0 >10,0 >5,0		
Desacoplo ⑤	dB	5-862 MHz 930-2150 MHz 2150-2400 MHz	>16,0 >17,0 >20,0		>18,0 >18,0 >22,0		>20,0 >30,0 >30,0	
Pérdidas de retorno	dB	5-862 MHz 930-2150 MHz 2150-2400 MHz	>12,0 >10,0 >14,0			>17,0 >12,0 >12,0		
Unidades por embalaje			6					
Peso embalaje	Kg		0,45					
Dimensiones embalaje	mm		155 x 95 x 40					