



CODIGO			9060046	9060047	9060048
MODELO			FP-414	FP-420	FP-426
Conexión			F hembra		
Salidas			4		
Rango de frecuencias	MHz		5 - 2400		
Atenuación de derivación ①	dB ±2,0	5-862 MHz 930-2150 MHz 2150-2400 MHz	14,0 14,0 15,0	20,0 20,0 20,5	26,0 26,0 25,0
Atenuación de paso ②	dB ±0,5	5-862 MHz 930-2150 MHz 2150-2400 MHz	4,5 4,5-5,7 5,7-6,5	1,2 1,2-2,6 2,6-3,0	0,8 0,8-1,8 1,8-2,3
Directividad ④	dB	5-862 MHz 930-2150 MHz 2150-2400 MHz	>13,0 >10,0 >10,0	>18,0 >10,0 >5,0	
Desacoplo ⑤	dB	5-862 MHz 930-2150 MHz 2150-2400 MHz	>16,0 >17,0 >20,0	>18,0 >18,0 >22,0	>20,0 >30,0 >30,0
Pérdidas de retorno	dB	5-862 MHz 930-2150 MHz 2150-2400 MHz	>12,0 >10,0 >14,0	>17,0 >12,0 >12,0	
Unidades por embalaje			6		
Peso embalaje	Kg		0,45		
Dimensiones embalaje	mm		155 x 95 x 40		