



CÓDIGO		9060063	9060064	9060065	9060066
MODELO		DE-201	DE-203	DE-205	DE-207
Conexión		F hembra			
Salidas		2			
Rango de frecuencias	MHz	5 - 2300			
Atenuación de derivación ①	dB ±1,5	5-47 MHz 11,0 47-862 MHz 11,5 950-2150 MHz 13,5 2150-2300 MHz 14,0	16,0 15,5 16,5 17,0	20,5 20,0 22,0 23,0	25,0 25,0 27,0 28,5
Planitud en banda	dB	±0,3			
Planitud en canal	dB	±0,1			
Atenuación de paso ②	dB ±0,5	5-47 MHz 3,0 47-862 MHz 2,5 950-2150 MHz 4,0 2150-2300 MHz 4,5	2,5 2,0 3,5 3,5	1,5 1,5 3,5 4,0	1,5 1,5 3,5 4,0
Directividad ④	dB	5-47 MHz >13 47-862 MHz >13 950-2150 MHz >5 2150-2300 MHz >5	>11 >12 >3 >2	>10 >7 >0 >0	>10 >5 >1 >0
Desacoplo ⑤	dB	5-47 MHz >33 47-862 MHz >30 950-2150 MHz >29 2150-2300 MHz >26	>42 >35 >33 >36	>52 >39 >35 >32	>60 >43 >34 >32
Pérdidas de retorno	dB	5-47 MHz >11 47-862 MHz >13 950-2150 MHz >9 2150-2300 MHz >8	>12 >15 >8 >8	>16 >15 >8 >8	>15 >12 >8 >8
Paso de corriente	V _~	24 max			
	mA	500 max			
	Tono	22 KHz/DiSEqC			
Índice de protección		IP 20			
Unidades por embalaje		12			
Peso embalaje	Kg	1,45			
Dimensiones embalaje	mm	195 x 115 x 67			