



CÓDIGO			9060063	9060064	9060065	9060066
MODELO			DE-201	DE-203	DE-205	DE-207
Conexión			F hembra			
Salidas			2			
Rango de frecuencias	MHz		5 - 2300			
Atenuación de derivación ①	dB ±1,5	5-47 MHz	11,0	16,0	20,5	25,0
		47-862 MHz	11,5	15,5	20,0	25,0
		950-2150 MHz	13,5	16,5	22,0	27,0
		2150-2300 MHz	14,0	17,0	23,0	28,5
Planitud en banda	dB		±0,3			
Planitud en canal	dB		±0,1			
Atenuación de paso ②	dB ±0,5	5-47 MHz	3,0	2,5	1,5	1,5
		47-862 MHz	2,5	2,0	1,5	1,5
		950-2150 MHz	4,0	3,5	3,5	3,5
		2150-2300 MHz	4,5	3,5	4,0	4,0
Directividad ④	dB	5-47 MHz	>13	>11	>10	>10
		47-862 MHz	>13	>12	>7	>5
		950-2150 MHz	>5	>3	>0	>1
		2150-2300 MHz	>5	>2	>0	>0
Desacoplo ⑤	dB	5-47 MHz	>33	>42	>52	>60
		47-862 MHz	>30	>35	>39	>43
		950-2150 MHz	>29	>33	>35	>34
		2150-2300 MHz	>26	>36	>32	>32
Pérdidas de retorno	dB	5-47 MHz	>11	>12	>16	>15
		47-862 MHz	>13	>15	>15	>12
		950-2150 MHz	>9	>8	>8	>8
		2150-2300 MHz	>8	>8	>8	>8
Paso de corriente	V _~		24 max			
	mA		500 max			
	Tono		22 KHz/DiSEqC			
Índice de protección			IP 20			
Unidades por embalaje			12			
Peso embalaje	Kg		1,45			
Dimensiones embalaje	mm		195 x 115 x 67			