



CÓDIGO			9060068	9060069	9060070	9060071
MODELO			DE-401	DE-403	DE-405	DE-407
Conexión			F hembra			
Salidas			4			
Rango de frecuencias	MHz		5 - 2300			
Atenuación de derivación ①	dB ±1,5	5-47 MHz	12,0	15,5	21,0	25,5
		47-862 MHz	12,5	15,5	20,5	25,0
		950-2150 MHz	15,0	17,5	22,5	28,5
		2150-2300 MHz	16,0	18,0	23,0	30,5
Planitud en banda	dB		±0,3			
Planitud en canal	dB		±0,1			
Atenuación de paso ②	dB ±0,5	5-47 MHz	5,0	2,5	1,5	1,0
		47-862 MHz	4,5	2,5	1,5	1,0
		950-2150 MHz	5,5	5,0	1,5	2,5
		2150-2300 MHz	6,0	5,5	2,0	3,0
Directividad ④	dB	5-47 MHz	>8	>25	>21	>11
		47-862 MHz	>22	>13	>11	>7
		950-2150 MHz	>10	>5	>6	>1
		2150-2300 MHz	>7	>5	>5	>0
Desacoplo ⑤	dB	5-47 MHz	>20	>18	>16	>15
		47-862 MHz	>22	>23	>22	>22
		950-2150 MHz	>21	>19	>18	>20
		2150-2300 MHz	>21	>21	>18	>19
Pérdidas de retorno	dB	5-47 MHz	>10	>10	>10	>12
		47-862 MHz	>10	>13	>11	>12
		950-2150 MHz	>9	>9	>10	>8
		2150-2300 MHz	>8	>9	>9	>7
Paso de corriente	V _~		24 max			
	mA		500 max			
	Tono		22 KHz/DiSEqC			
Indice de protección			IP 20			
Unidades por embalaje			12			
Peso embalaje	Kg		1,86			
Dimensiones embalaje	mm		375 x 85 x 67			