



CÓDIGO			9060073	9060074	9060075
MODELO			DE-603	DE-605	DE-607
Conexión			F hembra		
Solidas			6		
Rango de frecuencia	MHz		5 - 2300		
Atenuación de derivación ①	dB ±1,5	5-47 MHz	17,0	21,0	26,0
		47-862 MHz	17,5	21,0	25,0
		950-2150 MHz	21,0	24,5	27,5
		2150-2300 MHz	21,5	26,5	30,0
Planitud en banda	dB		±0,3		
Planitud en canal	dB		±0,1		
Atenuación de paso ②	dB ±0,5	5-47 MHz	4,0	1,5	1,5
		47-862 MHz	3,5	1,5	1,5
		950-2150 MHz	6,0	3,0	3,0
		2150-2300 MHz	7,5	3,5	3,5
Directividad ④	dB	5-47 MHz	>14	>12	>16
		47-862 MHz	>14	>10	>7
		950-2150 MHz	>0	>0	>0
		2150-2300 MHz	>0	>0	>0
Desacoplo ⑤	dB	5-47 MHz	>24	>24	>21
		47-862 MHz	>22	>24	>20
		950-2150 MHz	>20	>20	>21
		2150-2300 MHz	>22	>19	>25
Perdidas de retorno	dB	5-47 MHz	>10	>10	>10
		47-862 MHz	>10	>10	>11
		950-2150 MHz	>7	>8	>9
		2150-2300 MHz	>6	>7	>6
Paso de corriente	V _~		24 max		
	mA		500 max		
	Tono		22 KHz/DiSEqC		
Índice de protección			IP 20		
Unidades por embalaje			12		
Peso embalaje	Kg		2,88		
Dimensiones embalaje	mm		440 x 155 x 57		