



CÓDIGO			9060076	9060096	9060077	9060061	9060062
MODELO			DI-202	DI-302	DI-402	DI-602	DI-802
Conexión			F hembra				
Salidas			2	3	4	6	8
Rango de frecuencias	MHz		5 - 2300				
Atenuación de distribución ①	dB	5-47 MHz	4,5	7,5	8,5	10,5	12,5
		47-862 MHz	4,5	8,0	8,5	11,5	13,0
		950-2150 MHz	6,0	10,5	10,5	15,0	16,5
		2150-2300 MHz	6,5	11,0	11,5	16,5	17,5
Planitud en banda	dB		±0,3				
Planitud en canal	dB		±0,1				
Desacoplo ②	dB	5-47 MHz	>18	>19	>20	>22	>22
		47-862 MHz	>20	>20	>23	>23	>22
		950-2150 MHz	>18	>20	>18	>20	>20
		2150-2300 MHz	>18	>20	>15	>20	>20
Pérdida de retorno	dB	5-47 MHz	>10	>8	>10	>9	>9
		47-862 MHz	>10	>10	>13	>10	>9
		950-2150 MHz	>10	>10	>12	>10	>10
		2150-2300 MHz	>10	>10	>13	>10	>10
Paso de corriente	V=		24 max				
	mA		500 max				
	Tono		22 KHz / DiSEqC				
Índice de protección			IP 20				
Unidades por embalaje			12				
Peso embalaje	Kg		1,45	1,94	1,08	2,42	2,50
Dimensiones embalaje	mm		195 x 115 x 67	180 x 135 x 80	375 x 85 x 67	312 x 122 x 62	