



| CÓDIGO | | 9060055 | 9060078 | 9060056 | 9060079 | 9060057 | 9060058 | |
|------------------------------------|----------------|-----------------|-----------|-----------|-----------|-----------|---------|----------|
| MODELO | | FI-244 | | FI-474 | FI-594 | FI-254 | FI-484 | |
| Conexión | | F hembra | | | | | | |
| Salidas | | 2 | 3 | 4 | 5 | 2 | 4 | |
| Rango de frecuencias | MHz | 5 - 2400 | | | | | | |
| Atenuación y distribución ① | dB ±1,0 | 5-13 MHz | 4,5-4,5 | 7,5-7,5 | 10,0-10,0 | 11,0-11,0 | 5,0-5,0 | 14,0-9,5 |
| | | 13-47 MHz | 4,5-4,0 | 7,5-7,5 | 10,0-8,5 | 11,0-11,5 | 5,0-4,5 | 9,5-9,0 |
| | | 47-862 MHz | 4,0-4,5 | 7,5-9,0 | 8,5-9,0 | 11,5-13,0 | 4,5-4,0 | 9,0-8,0 |
| | | 950-2150 MHz | 4,5-5,5 | 9,0-10,5 | 9,0-11,0 | 13,0-15,0 | 4,0-4,0 | 8,0-10,0 |
| 2150-2400 MHz | 5,5-6,5 | 10,5-10,5 | 11,0-13,0 | 15,0-15,0 | 4,0-5,0 | 10,0-13,0 | | |
| Planitud de banda | dB | ±0,3 | | | | | | ±0,5 |
| Desacoplo ② | dB | 5-13 MHz | >18 | >20 | >26 | >20 | >9 | >14 |
| | | 13-47 MHz | >18 | >20 | >26 | >20 | >12 | >14 |
| | | 47-862 MHz | >20 | >21 | >15 | >22 | >13 | >12 |
| | | 950-2150 MHz | >18 | >23 | >16 | >24 | >15 | >8 |
| | | 2150-2400 MHz | >18 | >21 | >15 | >23 | >14 | >6 |
| Pérdidas de retorno | dB | 5-13 MHz | >17 | >16 | >19 | >15 | >13 | - |
| | | 13-47 MHz | >17 | >16 | >19 | >15 | >14 | >11 |
| | | 47-862 MHz | >15 | >11 | >13 | >11 | >15 | >12 |
| | | 950-2150 MHz | >12 | >11 | >16 | >11 | >14 | >11 |
| | | 2150-2400 MHz | >15 | >11 | >10 | >12 | >9 | >8 |
| Paso de corriente | V- | 34 max | | | | | | |
| | mA | 300 max | 400 max | 300 max | 400 max | 300 max | | |
| | Tono | 22 KHz / DiSEqC | | | | | | |
| Unidades por embalaje | | 6 | | | | | | |
| Peso embalaje | Kg | 0,45 | | | | | | |
| Dimensiones embalaje | mm | 155 x 95 x 40 | | | | | | |