



CÓDIGO			9060055	9060078	9060056	9060079	9060057	9060058	
MODELO			FI-244		FI-474	FI-594	FI-254	FI-484	
Conexión			F hembra						
Salidas			2	3	4	5	2	4	
Rango de frecuencias	MHz		5 - 2400						
Atenuación y distribución ①	dB ±1,0	5-13 MHz	4,5-4,5	7,5-7,5	10,0-10,0	11,0-11,0	5,0-5,0	14,0-9,5	
		13-47 MHz	4,5-4,0	7,5-7,5	10,0-8,5	11,0-11,5	5,0-4,5	9,5-9,0	
		47-862 MHz	4,0-4,5	7,5-9,0	8,5-9,0	11,5-13,0	4,5-4,0	9,0-8,0	
		950-2150 MHz	4,5-5,5	9,0-10,5	9,0-11,0	13,0-15,0	4,0-4,0	8,0-10,0	
		2150-2400 MHz	5,5-6,5	10,5-10,5	11,0-13,0	15,0-15,0	4,0-5,0	10,0-13,0	
Planitud de banda	dB		±0,3						±0,5
Desacoplo ②	dB	5-13 MHz	>18	>20	>26	>20	>9	>14	
		13-47 MHz	>18	>20	>26	>20	>12	>14	
		47-862 MHz	>20	>21	>15	>22	>13	>12	
		950-2150 MHz	>18	>23	>16	>24	>15	>8	
		2150-2400 MHz	>18	>21	>15	>23	>14	>6	
Pérdidas de retorno	dB	5-13 MHz	>17	>16	>19	>15	>13	-	
		13-47 MHz	>17	>16	>19	>15	>14	>11	
		47-862 MHz	>15	>11	>13	>11	>15	>12	
		950-2150 MHz	>12	>11	>16	>11	>14	>11	
		2150-2400 MHz	>15	>11	>10	>12	>9	>8	
Paso de corriente	V-		34 max						
	mA		300 max	400 max	300 max	400 max	300 max		
	Tono		22 KHz / DiSEqC						
Unidades por embalaje			6						
Peso embalaje	Kg		0,45						
Dimensiones embalaje	mm		155 x 95 x 40						