



CODIGO		9070004	9070005	9070006	9070008	
MODELO		BS-220	BS-420	BS-620	BS-820	
Instalación		Final	Intermedia			
Conexión		Borna y puente				
Conectores de salida	C1	IEC macho Ø9,52 mm				
	C2	IEC hembra Ø9,52 mm				
Rango de frecuencias	MHz	E/S	5 - 2400			
		C1	5 - 2400			
		C2	5 - 2400			
Atenuación	dB ±TOL	FM	11,0 ±1,0	16,5 ±1,0	21,0 ±1,0	31,0 ±1,0
		TV	11,0 ±1,0	16,5 ±1,0	21,0 ±1,0	31,0 ±1,0
		SAT	11,5 ±1,5	17,5 ±1,5	22,5 ±2,0	35,0 ±4,5
Atenuación de paso	dB ±TOL	FM	-	0,9 ±0,3		
		TV	-	0,9 ±0,3		
		SAT	-	1,4 ±0,6		
Directividad	dB	FM	-	>10		>10
		TV	-	>10		>10
		SAT	-	>10		>5
Desacoplo	dB	FM	>15	>15		
		TV	>15	>15		
		SAT	>17	>15		
Pérdidas de retorno	dB	FM	>24	>15		
		TV	>24	>15		
		SAT	>14	>14		
Unidades por embalaje		24				
Peso embalaje	Kg	2,2				
Dimensiones embalaje	mm	305 x 225 x 65				