



CODIGO			9070037		9070039		9070038		9070040		9070041		9070042	
MODELO			BM-100		BM-111		BM-101		BM-200		BM-500		BM-700	
Instalación			Final						Intermedia					
Conexión			Borna y puente											
Conectores de salida			C1	IEC macho Ø9,52 mm										
		C2	IEC hembra Ø9,52 mm											
Rango de frecuencias		MHz	E/S	5 - 862				13 - 862		5 - 862				
			C1	5 - 862				13 - 862		5 - 862				
			C2	5 - 232			5 - 862		13 - 862		5 - 862			
Atenuación ①		dB ±TOL	FM	10,0 ±0,7	10,0 ±0,7	6,0 ±0,5	25,0 ±1,5	30,0 ±0,2	34,0 ±2,0					
			DAB	10,0 ±1,5	10,0 ±1,5	6,0 ±0,5	25,0 ±1,5	30,0 ±0,2	34,0 ±2,0					
			VHF	4,0 ±1,5	1,5 ±1,0	6,0 ±0,5	8,0 ±0,7	11,0 ±1,0	16,0 ±1,0					
			UHF	3,0 ±0,5	0,5 ±0,2	5,5 ±0,7	8,0 ±0,7	10,5 ±1,0	15,5 ±1,0					
Atenuación de paso ②		dB ±TOL	FM	-		6,5 ±0,5	2,0 ±0,3	1,0 ±0,2	0,7 ±0,2					
			VHF	-		6,5 ±0,7	2,0 ±0,5	1,1 ±0,3	0,7 ±0,2					
			UHF	-		5,5 ±0,7	2,0 ±0,5	1,3 ±0,4	0,9 ±0,3					
Directividad ③		dB	FM	-		0	>12	>25	>21					
			TV	-		0	>9	>13						
Desacoplo ④		dB	FM	>14	>9	>5,5	>16	>20	>21					
			TV	>14	>9	>5,5	>15	>18	>19					
Pérdidas de retorno		dB	FM	>18	>12	>6,0	>12	>18	>20					
			TV	>10	>12	>5,5	>12	>15	>16					
Unidades por embalaje			24											
Peso embalaje		Kg	2,2											
Dimensiones embalaje		mm	305 x 225 x 65											