



CODIGO		9070037	9070039	9070038	9070040	9070041	9070042	
MODELO		BM-100	BM-111	BM-101	BM-200	BM-500	BM-700	
Instalación		Final			Intermedia			
Conexión		Borna y puente						
Conectores de salida	C1	IEC macho Ø9,52 mm						
	C2	IEC hembra Ø9,52 mm						
Rango de frecuencias	MHz	E/S	5 - 862		13 - 862	5 - 862		
		C1	5 - 862		13 - 862	5 - 862		
		C2	5 - 232		5 - 862	13 - 862	5 - 862	
Atenuación ①	dB ±TOL	FM	10,0 ±0,7	10,0 ±0,7	6,0 ±0,5	25,0 ±1,5	30,0 ±0,2	34,0 ±2,0
		DAB	10,0 ±1,5	10,0 ±1,5	6,0 ±0,5	25,0 ±1,5	30,0 ±0,2	34,0 ±2,0
		VHF	4,0 ±1,5	1,5 ±1,0	6,0 ±0,5	8,0 ±0,7	11,0 ±1,0	16,0 ±1,0
		UHF	3,0 ±0,5	0,5 ±0,2	5,5 ±0,7	8,0 ±0,7	10,5 ±1,0	15,5 ±1,0
Atenuación de paso ②	dB ±TOL	FM	-		6,5 ±0,5	2,0 ±0,3	1,0 ±0,2	0,7 ±0,2
		VHF	-		6,5 ±0,7	2,0 ±0,5	1,1 ±0,3	0,7 ±0,2
		UHF	-		5,5 ±0,7	2,0 ±0,5	1,3 ±0,4	0,9 ±0,3
Directividad ③	dB	FM	-		0	>12	>25	>21
		TV	-		0	>9	>13	
Desacoplo ④	dB	FM	>14	>9	>5,5	>16	>20	>21
		TV	>14	>9	>5,5	>15	>18	>19
Pérdidas de retorno	dB	FM	>18	>12	>6,0	>12	>18	>20
		TV	>10	>12	>5,5	>12	>15	>16
Unidades por embalaje		24						
Peso embalaje	Kg	2,2						
Dimensiones embalaje	mm	305 x 225 x 65						