



CODIGO			9070037		9070039		9070038		9070040		9070041		9070042	
MODELO			BM-100		BM-111		BM-101		BM-200		BM-500		BM-700	
Instalación					Final					Intermedia				
Conexión					Borna y puente									
Conectores de salida				C1	IEC macho Ø9,52 mm									
				C2	IEC hembra Ø9,52 mm									
Rango de frecuencias			MHz	E/S	5 - 862				13 - 862		5 - 862			
				C1	5 - 862				13 - 862		5 - 862			
				C2	5 - 232			5 - 862		13 - 862		5 - 862		
Atenuación ①			dB ±TOL	FM	10,0 ±0,7	10,0 ±0,7	6,0 ±0,5	25,0 ±1,5	30,0 ±0,2	34,0 ±2,0				
				DAB	10,0 ±1,5	10,0 ±1,5	6,0 ±0,5	25,0 ±1,5	30,0 ±0,2	34,0 ±2,0				
				VHF	4,0 ±1,5	1,5 ±1,0	6,0 ±0,5	8,0 ±0,7	11,0 ±1,0	16,0 ±1,0				
				UHF	3,0 ±0,5	0,5 ±0,2	5,5 ±0,7	8,0 ±0,7	10,5 ±1,0	15,5 ±1,0				
Atenuación de paso ②			dB ±TOL	FM	-			6,5 ±0,5	2,0 ±0,3	1,0 ±0,2	0,7 ±0,2			
				VHF	-			6,5 ±0,7	2,0 ±0,5	1,1 ±0,3	0,7 ±0,2			
				UHF	-			5,5 ±0,7	2,0 ±0,5	1,3 ±0,4	0,9 ±0,3			
Directividad ③			dB	FM	-			0	>12	>25	>21			
				TV	-			0	>9	>13				
Desacoplo ④			dB	FM	>14	>9	>5,5	>16	>20	>21				
				TV	>14	>9	>5,5	>15	>18	>19				
Pérdidas de retorno			dB	FM	>18	>12	>6,0	>12	>18	>20				
				TV	>10	>12	>5,5	>12	>15	>16				
Unidades por embalaje					24									
Peso embalaje			Kg		2,2									
Dimensiones embalaje			mm		305 x 225 x 65									