



CODIGO			9070099		9070043	9070046	9070044		9070045	
MODELO			BC-101		BC-100	BC-110	BC-200		BC-500	
Instalación					Final			Intermedia		
Conexión					Borna y puente					
Conectores de salida			C1	IEC macho Ø9,52 mm						
			C2	IEC hembra Ø9,52 mm						
Rango de frecuencias		MHz	E/S	5 - 1000						
			C1	5-15/118-1000	5 - 68 / 118 -1000					
			C2	87,5-108,0						
Atenuación ①		dB ±TOL	R	0,7 ±0,1	0,3 ±0,1	5,0 ±0,5	11,0 ±1,0	17,0 ±2,0		
			FM	1,1 ±0,3	1,1 ±0,3	6,0 ±1,0	11,5 ±1,0	17,0 ±2,0		
			TV	1,3 ±0,4	0,9 ±0,3	5,5 ±0,7	10,0 ±1,5	15,0 ±2,0		
Atenuación de paso ②		dB ±TOL	R	-			1,0 ±0,2	0,8 ±0,2		
			FM	-			1,0 ±0,2	0,7 ±0,2		
			TV	-			1,4 ±0,4	1,0 ±0,3		
Directividad ③		dB	FM	-			>25	>21		
			TV	-			>13	>12		
Desacoplo ④		dB	FM	>18						
			TV	>16						
Selectividad		dB	FM	>10						
			TV	>18						
Pérdidas de retorno		dB	R	>10	>18					
			FM	>12	>16	>20	>18	>20		
			TV	>10	>18				>20	
Aislamiento		Kv		2	-					
Retardo croma-luminancia		ns		<10						
Unidades por embalaje				24						
Peso embalaje		Kg		2,2						
Dimensiones embalaje		mm		305 x 225 x 65						