



CODIGO			9070062	9070073	9070068	9070069	9070070	9070071	
MODELO			BS-100	BS-112	BS-110	BS-111	BS-210	BS-510	
Instalación			Final				Intermedia		
Conexión			Borna y puente						
Conectores de salida		C1	IEC macho Ø9,52 mm						
		C2	F hembra	IEC hembra Ø9,52 mm					
Rango de frecuencias		E/S	5 - 2400			5 - 2400			
		C1	5 - 862			5 - 2400			
		C2	930 - 2400			5 - 2400			
Atenuación ①		dB ±TOL	FM	0,2±0,1		3,7 ±0,3		10,0 ±1,0	14,5 ±0,5
			TV	1,0±0,5		4,0 ±0,5		10,0 ±1,0	14,5 ±1,0
			SAT	1,2±0,6		5,0 ±1,2		12,0 ±2,0	15,0 ±2,0
Atenuación de paso ②		dB ±TOL	FM	-			2,5 ±0,5	1,0 ±0,2	
			TV	-			2,5 ±0,7	1,0 ±0,3	
			SAT	-			3,0 ±1,0	2,0 ±1,0	
Directividad ③		dB	FM	-			>20,0	>25,5	
			TV	-			>12,0	>13,5	
			SAT	-			>5,0	>5,0	
Desacoplo ④		dB	FM	>45		>20	>15	>45	>13
			TV	>14		>20	>10	>30	>13
			SAT	>14		>14	>8	>28	>13
Selectividad ⑥ ⑦		dB	TV-R	>15		-			
			SAT	>15		-			
Pérdidas de retorno		dB	VR	>25		>16	-	>13	>16
			FM	>25		>16	>13	>13	>16
			TV	>14		>16	>12	>12	>16
			SAT	>10		>9	>9	>12	>16
Paso de corriente		V~	34 max						
		mA	500 max						
		Tono	22 KHz / DiSEqC						
Unidades por embalaje			24						
Peso embalaje		Kg	2,2						
Dimensiones embalaje		mm	305 x 225 x 65						