



CÓDIGO			9070100	9070101	9070102	9070103	9070104	9070084	9070085
MODELO			PT-110	PT-210	PT-310	PT-410	PT-510	PT-600	PT-800
Conexión			F hembra						
Salidas			1	2	3	4	5	6	8
Rango de frecuencias	MHz		5 - 2300						
Atenuación de derivación ①	dB ±1,5	5-47 MHz	0,3	3,5	7,5	8,5	11,5	11,5	12,5
		47-862 MHz	0,3	4,0	7,0	8,5	11,0	11,0	12,5
		950-2150 MHz	0,7	5,5	10,0	10,5	14,5	14,5	16,0
		2150-2300 MHz	0,7	6,0	10,5	11,5	15,0	15,5	16,5
Planitud en banda	dB		±0,2	±0,3					
Planitud en canal	dB		±0,1						
Desacoplo ⑤	dB	5-47 MHz	-	>16	>19	>20	>26	>26	>22
		47-862 MHz	-	>28	>23	>29	>26	>25	>25
		950-2150 MHz	-	>22	>20	>16	>25	>24	>18
		2150-2300 MHz	-	>20	>25	>18	>27	>27	>17
Pérdidas de retorno	dB	5-47 MHz	>37	>15	>10	>10	>10	>10	>10
		47-862 MHz	>25	>15	>14	>12	>12	>12	>11
		950-2150 MHz	>13	>11	>12	>9	>9	>8	>10
		2150-2300 MHz	>14	>9	>12	>9	>9	>7	>10
Índice de protección			IP 20						
Unidades por embalaje			12		12		12	12	
Peso embalaje	Kg		1,01		1,37		1,98	2,40	
Dimensiones embalaje	mm		255 x 70 x 90		250 x 85 x 90		260x125x750	260 x 125 x 90	