



CÓDIGO		9130069		9130070		9130071		9130072		9130073	
MODELO		MB-202		MB-203		MB-204		MB-205		MB-206	
Sistema de TV		FM-TV / DVB-S / AM-TV / DVB-T									
Conexión		F hembra									
Entradas		9									
Salidas derivadas		8		12		16		20		24	
Rango de frecuencias	MHz	47-862	950-2150	47-862	950-2150	47-862	950-2150	47-862	950-2150	47-862	950-2150
Atenuación de derivación	dB±TOL	0 ±3,0	0 ±3,0	0 ±3,0	1 ±3,0	0 ±3,0	1 ±3,0	2 ±3,0	2 ±3,0	2 ±3,0	2 ±3,0
Nivel de salida	dBµV	95 (DIN 45004B)	100 (IMD ₂ -35 dB) 95 (IMD ₂ -35 dB)	92 (DIN 45004B)	100 (IMD ₂ -35 dB) 92 (IMD ₂ -35 dB)	92 (DIN 45004B)	100 (IMD ₂ -35 dB) 92 (IMD ₂ -35 dB)	91 (DIN 45004B)	100 (IMD ₂ -35 dB) 91 (IMD ₂ -35 dB)	91 (DIN 45004B)	100 (IMD ₂ -35 dB) 91 (IMD ₂ -35 dB)
Rechazo entre bandas	dB	> 25 TV/SAT > 65 SAT/TV									
Desacoplo entre usuarios	dB	> 25 TV > 30 SAT									
Desacoplo de conmutación	dB	> 30 SAT/SAT									
Conmutación de las salidas		DiSEqC 2.0 14V $\pm$ /18V $\pm$ 0/22 kHz									
Alimentación de las LNB		1000 mA / 16V $\pm$									
Tensión de salida	V $\pm$	16V $\pm$									
Consumo desde el receptor	mA	40 ±2,0 (14/18V $\pm$)									
Temperatura en proximidad del equipo	°C	-10..+65									
Temperatura ambiente con/sin ventilador	°C	-10..+55/+45									
Índice de protección		IP 30									
Unidades por embalaje		1	5	1	5	1	5	1	5	1	5
Peso embalaje	Kg	0,86	4,46	1,10	5,95	1,12	6,10	1,38	7,35	1,40	7,45
Dimensiones embalaje	mm	260x245x55	290x270x270	335x245x55	345x300x270	335x245x55	345x300x270	395x245x55	400x290x270	395x245x55	400x290x270