



CÓDIGO		9130079		9130080		9130081		9130082		9130083	
MODELO		MB-302		MB-303		MB-304		MB-305		MB-306	
Sistema de TV		FM-TV / DVB-S / AM-TV / DVB-T									
Conexión		F hembra									
Entradas		13									
Salidas derivadas		8		12		16		20		24	
Rango de frecuencias	MHz	47-862	950-2150	47-862	950-2150	47-862	950-2150	47-862	950-2150	47-862	950-2150
Atenuación de derivación	dB±TOL	0 ±2,0	0 ±2,0	1 ±2,0	1 ±2,0	1 ±2,0	1 ±2,0	2 ±2,0	2 ±2,0	2 ±2,0	2 ±2,0
Ecualización de derivación	dB	3	3	2	3	2	3	1	2	1	2
Nivel de salida	dBµV	95 (DIN 45004B)	100 (IMD ₃ -35 dB) 90 (IMD ₂ -35 dB)	92 (DIN 45004B)	100 (IMD ₃ -35 dB) 90 (IMD ₂ -35 dB)	92 (DIN 45004B)	100 (IMD ₃ -35 dB) 90 (IMD ₂ -35 dB)	91 (DIN 45004B)	100 (IMD ₃ -35 dB) 90 (IMD ₂ -35 dB)	91 (DIN 45004B)	100 (IMD ₃ -35 dB) 90 (IMD ₂ -35 dB)
Rechazo entre bandas	dB	> 25 TV/SAT > 65 SAT/TV									
Desacoplo entre usuarios	dB	> 25 TV > 30 SAT									
Desacoplo de conmutación	dB	> 30 SAT/SAT									
Conmutación de las salidas		DiSEqC 2.0 14V---/18V--- 0/22 kHz									
Alimentación de las LNB		2000 mA /13 V---									
Tensión de salida	V---	13 V---									
Consumo desde el receptor	mA	40 ±2,0 (14/18V---									
Temperatura en proximidad del equipo	°C	-10..+65									
Temperatura ambiente con/sin ventilador	°C	-10..+55/+45									
Índice de protección		IP 30									
Unidades por embalaje		1	5	1	5	1	5	1	5	1	5
Peso embalaje	Kg	1,19	6,50	1,44	7,75	1,46	7,80	1,70	9,03	1,72	9,13
Dimensiones embalaje	mm	333x245x55	345x305x270	333x245x55	345x305x270	333x245x55	345x305x270	395x245x55	400x290x270	395x245x55	400x290x270