



CÓDIGO		9130094		9130095		9130096		9130097		9130098	
MODELO		ML-202		ML-203		ML-204		ML-205		ML-206	
Sistema de TV		FM-TV / DVB-S / AM-TV / DVB-T									
Conexión		F hembra									
Entradas		9									
Salidas		9									
Salidas derivadas		8		12		16		20		24	
Rango de frecuencias	MHz	47-862	950-2150	47-862	950-2150	47-862	950-2150	47-862	950-2150	47-862	950-2150
Atenuación de derivación	dB±TOL	0 ±3,0	0 ±3,0	0 ±3,0	1 ±3,0	0 ±3,0	1 ±3,0	2 ±3,0	2 ±3,0	2 ±3,0	2 ±3,0
Atenuación de paso	dB	-2,5 ±3,5	1,9 ±1,0	-0,8 ±3,2	3,4 ±1,7	-0,8 ±3,2	3,4 ±1,7	-4,1 ±4,4	4,9 ±2,5	-4,1 ±4,4	4,9 ±2,5
Nivel de salida	dBµV	95 (DIN 45004B)	100 (IMD ₃ -35 dB) 95 (IMD ₂ -35 dB)	92 (DIN 45004B)	100 (IMD ₃ -35 dB) 92 (IMD ₂ -35 dB)	92 (DIN 45004B)	100 (IMD ₃ -35 dB) 92 (IMD ₂ -35 dB)	91 (DIN 45004B)	100 (IMD ₃ -35 dB) 91 (IMD ₂ -35 dB)	91 (DIN 45004B)	100 (IMD ₃ -35 dB) 91 (IMD ₂ -35 dB)
Rechazo entre bandas	dB	> 25 TV/SAT > 65 SAT/TV									
Desacoplo entre usuarios	dB	> 25 TV > 30 SAT									
Desacoplo de conmutación	dB	> 30 SAT/SAT									
Conmutación de las salidas		DiSEqC 2.0 14V≡/18V≡ 0/22 kHz									
Alimentación de las LNB		1000 mA /16 V≡									
Consumo desde el receptor	mA	40 ±2,0 (14/18V≡)									
Temperatura en proximidad del equipo	°C	-10..+65									
Temperatura ambiente con/sin ventilador	°C	-10..+55/+45									
Índice de protección		IP 30									
Unidades por embalaje		1	5	1	5	1	5	1	5	1	5
Peso embalaje	Kg	0,75	4,15	0,85	4,65	0,95	5,15	1,15	6,15	1,25	6,65
Dimensiones embalaje	mm	260x245x55	285x245x260	260x245x55	285x245x260	260x245x55	285x245x260	335x245x55	340x290x260	335x250x55	340x290x260