



CÓDIGO		9130134		9130135		9130136		9130137		9130138	
MODELO		ML-402		ML-403		ML-404		ML-405		ML-406	
Sistema de TV		FM-TV / DVB-S / AM-TV / DVB-T									
Conexión		F hembra									
Entradas		17									
Salidas		17									
Salidas derivadas		8		12		16		20		24	
Rango de frecuencias	MHz	47-862	950-2150	47-862	950-2150	47-862	950-2150	47-862	950-2150	47-862	950-2150
Atenuación de derivación	dB±TOL	2 ±2,0	0 ±2,0	4 ±2,0	1 ±2,0	4 ±2,0	1 ±2,0	6 ±2,0	2 ±2,0	6 ±2,0	2 ±2,0
Ecualización de derivación	dB	3	3	2	3	2	3	1	2	1	2
Atenuación de paso	dB	4,5 ±1,0	2 ±1,0	4,5 ±1,0	3 ±1,0	4,5 ±1,0	3 ±1,0	4,5 ±1,0	4 ±1,0	4,5 ±1,0	4 ±1,0
Nivel de salida	dBµV	95 (DIN 45004B)	100 (IMD ₃ -35 dB) 90 (IMD ₂ -35 dB)	92 (DIN 45004B)	100 (IMD ₃ -35 dB) 90 (IMD ₂ -35 dB)	92 (DIN 45004B)	100 (IMD ₃ -35 dB) 90 (IMD ₂ -35 dB)	91 (DIN 45004B)	100 (IMD ₃ -35 dB) 90 (IMD ₂ -35 dB)	91 (DIN 45004B)	100 (IMD ₃ -35 dB) 90 (IMD ₂ -35 dB)
Rechazo entre bandas	dB	> 25 TV/SAT > 65 SAT/TV									
Desacoplo entre usuarios	dB	> 25 TV > 30 SAT									
Desacoplo de conmutación	dB	> 30 SAT/SAT									
Conmutación de las salidas		DiSEqC 2.0 14V $\overline{=}$ /18V $\overline{=}$ 0/22 kHz									
Alimentación de las LNB		2000 mA /13 V $\overline{=}$									
Consumo desde el receptor	mA	40 ±2,0 (14/18V $\overline{=}$)									
Temperatura en proximidad del equipo	°C	-10..+65									
Temperatura ambiente con/sin ventilador	°C	-10..+55/+45									
Índice de protección		IP 30									
Unidades por embalaje		1	5	1	5	1	5	1	5	1	5
Peso embalaje	Kg	1,05	5,65	1,15	6,15	1,30	7	1,51	8,05	1,65	8,75
Dimensiones embalaje	mm	335x245x55	340x290x260	335x245x55	340x290x260	335x245x55	340x290x260	395x245x55	340x290x260	395x245x55	340x290x260