



| CÓDIGO                                  |        | 9130134                                                                                                    |                                                                     | 9130135            |                                                                     | 9130136            |                                                                     | 9130137            |                                                                     | 9130138            |                                                                     |
|-----------------------------------------|--------|------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------|--------------------|---------------------------------------------------------------------|--------------------|---------------------------------------------------------------------|--------------------|---------------------------------------------------------------------|--------------------|---------------------------------------------------------------------|
| MODELO                                  |        | ML-402                                                                                                     |                                                                     | ML-403             |                                                                     | ML-404             |                                                                     | ML-405             |                                                                     | ML-406             |                                                                     |
| Sistema de TV                           |        | FM-TV / DVB-S / AM-TV / DVB-T                                                                              |                                                                     |                    |                                                                     |                    |                                                                     |                    |                                                                     |                    |                                                                     |
| Conexión                                |        | F hembra                                                                                                   |                                                                     |                    |                                                                     |                    |                                                                     |                    |                                                                     |                    |                                                                     |
| Entradas                                |        | 17                                                                                                         |                                                                     |                    |                                                                     |                    |                                                                     |                    |                                                                     |                    |                                                                     |
| Salidas                                 |        | 17                                                                                                         |                                                                     |                    |                                                                     |                    |                                                                     |                    |                                                                     |                    |                                                                     |
| Salidas derivadas                       |        | 8                                                                                                          |                                                                     | 12                 |                                                                     | 16                 |                                                                     | 20                 |                                                                     | 24                 |                                                                     |
| Rango de frecuencias                    | MHz    | 47-862                                                                                                     | 950-2150                                                            | 47-862             | 950-2150                                                            | 47-862             | 950-2150                                                            | 47-862             | 950-2150                                                            | 47-862             | 950-2150                                                            |
| Atenuación de derivación                | dB±TOL | 2 ±2,0                                                                                                     | 0 ±2,0                                                              | 4 ±2,0             | 1 ±2,0                                                              | 4 ±2,0             | 1 ±2,0                                                              | 6 ±2,0             | 2 ±2,0                                                              | 6 ±2,0             | 2 ±2,0                                                              |
| Ecualización de derivación              | dB     | 3                                                                                                          | 3                                                                   | 2                  | 3                                                                   | 2                  | 3                                                                   | 1                  | 2                                                                   | 1                  | 2                                                                   |
| Atenuación de paso                      | dB     | 4,5 ±1,0                                                                                                   | 2 ±1,0                                                              | 4,5 ±1,0           | 3 ±1,0                                                              | 4,5 ±1,0           | 3 ±1,0                                                              | 4,5 ±1,0           | 4 ±1,0                                                              | 4,5 ±1,0           | 4 ±1,0                                                              |
| Nivel de salida                         | dBµV   | 95<br>(DIN 45004B)                                                                                         | 100<br>(IMD <sub>3</sub> -35 dB)<br>90<br>(IMD <sub>2</sub> -35 dB) | 92<br>(DIN 45004B) | 100<br>(IMD <sub>3</sub> -35 dB)<br>90<br>(IMD <sub>2</sub> -35 dB) | 92<br>(DIN 45004B) | 100<br>(IMD <sub>3</sub> -35 dB)<br>90<br>(IMD <sub>2</sub> -35 dB) | 91<br>(DIN 45004B) | 100<br>(IMD <sub>3</sub> -35 dB)<br>90<br>(IMD <sub>2</sub> -35 dB) | 91<br>(DIN 45004B) | 100<br>(IMD <sub>3</sub> -35 dB)<br>90<br>(IMD <sub>2</sub> -35 dB) |
| Rechazo entre bandas                    | dB     | > 25 TV/SAT<br>> 65 SAT/TV                                                                                 |                                                                     |                    |                                                                     |                    |                                                                     |                    |                                                                     |                    |                                                                     |
| Desacoplo entre usuarios                | dB     | > 25 TV<br>> 30 SAT                                                                                        |                                                                     |                    |                                                                     |                    |                                                                     |                    |                                                                     |                    |                                                                     |
| Desacoplo de conmutación                | dB     | > 30 SAT/SAT                                                                                               |                                                                     |                    |                                                                     |                    |                                                                     |                    |                                                                     |                    |                                                                     |
| Conmutación de las salidas              |        | DiSEqC 2.0<br>14V $\overline{\overline{\phantom{0}}}$ /18V $\overline{\overline{\phantom{0}}}$<br>0/22 kHz |                                                                     |                    |                                                                     |                    |                                                                     |                    |                                                                     |                    |                                                                     |
| Alimentación de las LNB                 |        | 2000 mA /13 V $\overline{\overline{\phantom{0}}}$                                                          |                                                                     |                    |                                                                     |                    |                                                                     |                    |                                                                     |                    |                                                                     |
| Consumo desde el receptor               | mA     | 40 ±2,0<br>(14/18V $\overline{\overline{\phantom{0}}}$ )                                                   |                                                                     |                    |                                                                     |                    |                                                                     |                    |                                                                     |                    |                                                                     |
| Temperatura en proximidad del equipo    | °C     | -10..+65                                                                                                   |                                                                     |                    |                                                                     |                    |                                                                     |                    |                                                                     |                    |                                                                     |
| Temperatura ambiente con/sin ventilador | °C     | -10..+55/+45                                                                                               |                                                                     |                    |                                                                     |                    |                                                                     |                    |                                                                     |                    |                                                                     |
| Índice de protección                    |        | IP 30                                                                                                      |                                                                     |                    |                                                                     |                    |                                                                     |                    |                                                                     |                    |                                                                     |
| Unidades por embalaje                   |        | 1                                                                                                          | 5                                                                   | 1                  | 5                                                                   | 1                  | 5                                                                   | 1                  | 5                                                                   | 1                  | 5                                                                   |
| Peso embalaje                           | Kg     | 1,05                                                                                                       | 5,65                                                                | 1,15               | 6,15                                                                | 1,30               | 7                                                                   | 1,51               | 8,05                                                                | 1,65               | 8,75                                                                |
| Dimensiones embalaje                    | mm     | 335x245x55                                                                                                 | 340x290x260                                                         | 335x245x55         | 340x290x260                                                         | 335x245x55         | 340x290x260                                                         | 395x245x55         | 340x290x260                                                         | 395x245x55         | 340x290x260                                                         |