



CODIGO		9040017			9040025		
MODELO		DA-711			DA-713		
Rango de frecuencias	Banda	VR	TV	SAT	VR	TV	SAT
	MHz	5-30	47-862	930-2.150	5-65	86-862	930-2.150
Ganancia	dB±TOL	4 ±0,5	34 ±1,0	41 ±2,5	6 ±0,5	34 ±1,0	41 ±2,5
Planitud en banda	dB	±0,5	±0,8	±2,0	±0,5	±0,8	±2,0
Regulación de ganancia	dB	-	20	15	-	20	15
Ecualización fija	dB	2,5	-	1,5 ±1,5	3,5	-	1,5 ±1,5
Margen de ecualización	dB	-	17	10	-	16	10
Test de entrada/salida	dB±TOL	-30 ±0,5	-30 ±2,0		-30 ±0,5	-30 ±2,0	
Nivel de salida	dBµV	107 DIN 45004B 104 (IMD ₃ -60 dB) 90 (IMD ₂ -60 dB)	120 DIN 45004B 117 (IMD ₃ -60 dB) 110 (IMD ₂ -60 dB) 105 (CTB -60 dB) 105 (CSO -60 dB) 104 (XMOD -60 dB)	120 (IMD ₃ -35 dB) 110 (IMD ₂ -35 dB)	107 DIN 45004B 104 (IMD ₃ -60 dB) 90 (IMD ₂ -60 dB)	120 DIN 45004B 117 (IMD ₃ -60 dB) 110 (IMD ₂ -60 dB) 105 (CTB -60 dB) 105 (CSO -60 dB) 104 (XMOD -60 dB)	120 (IMD ₃ -35 dB) 110 (IMD ₂ -35 dB)
Pérdidas de retorno E/S	dB	≥14	≥10	≥9	≥14	≥10	≥9
Retardo croma-luminancia	ns	<40					
Figura de ruido	dB	-7		-10	-7		-10
Fusible	V~	250					
	W	5					
Tensión de red	V~	230 ±15% 50/60 Hz					
	VA	12					
Temperatura de funcionamiento	°C	-20...+65					
Indice de protección		IP 50D					
Unidades por embalaje		1					
Peso embalaje	Kg	1,8					
Dimensiones embalaje	mm	220 x 200 x 60					